

## **NASA DUAL-USE PROGRAM HELPS DEVELOP TECHNOLOGY FOR COLLECTING REAL-TIME TEST DATA**

High-speed data provides valuable information about tests conducted with rocket engines and other propulsion components. Providing timely access to this data has been an issue in the past. Through the Dual-Use Development Program at NASA's Stennis Space Center (SSC), direct-to-disk storing capabilities for high speed data acquisition systems are now available through Integrated Systems Consultant's (ISC) TAXI-100 Direct-to-Disk system. The TAXI-100 Direct- to-Disk system works through the Racal Storeplex system in conjunction with system integration software, Disk Recording System (DRS), developed by Boeing test operations at SSC to provide the high-speed data significantly faster with fewer errors than was available with the previously used Racal Storeplex tape recordings.

The TAXI-100 Direct-to-Disk system was developed jointly by Integrated Systems Consultants (ISC) of San Jose, CA, and Omni Technologies of New Orleans, LA. under a Cooperative Agreement NCC13-00006 with the NASA Office of Technology Transfer. The system has a real-time remote hardware demultiplexing capability that provides channelized data to the control station across a fiber optic link. The Cooperative Agreement between NASA, ISC and Omni, who developed the fiber optic interface, provides acquisition solutions for customers using coax to fiber conversion solutions such as the FOTR-125 fiber link. The TAXI-100 card developed by ISC provides PC-based direct-to-disk solutions for the Racal Storeplex system and other acquisition front-ends for industry where sustained data streams of 10 Mbytes per second or more are required.

## **PROBLEM DESCRIPTION**

NASA rocket testing at Stennis Space Center requires acquisition of high-speed data during tests with the ability to transfer high-volume data to remote control stations and engineering management. The control, data recording, and data post-processing equipment of the facility are located in a control room at a safe distance from the test stand. Heretofore, the transfer of data from the instrumentation to the post-processing equipment has entailed post-test downloading of the data from Racal tapes via software, requiring many hours to days of post-test reduction before the data could be viewed in a channelized format. In addition, hours were spent in pre-test preparation of the recording tapes to ensure their integrity. Despite these efforts, there were occasions where single sample errors were introduced into the data by the tapes.

The present high-speed data acquisition system uses Racal Storeplex Recorders, which are commercially available multichannel recorders. Racal has now discontinued that product line. Racal methods involve the use of real-time programmable logic of the parallel bus within the Racal recorder. Without extensive modifications, the test stand configuration required that the high-speed data continue to route through the Racal Storeplex tape transport units.

One method of demultiplexing the data using the Racal Storeplex system required the fabrication of a new card as an interface to existing commercial off the shelf products (COTS) to extract the channelized data from the proprietary format. The TAXI bus is a serial bus used between the Racal front-end and the recording unit. By extracting the data from the Racal front-end, the data can then be recorded directly to disk, which

provides a recording media that requires less pretest maintenance and is less susceptible to sample recording errors.

## **SOLUTION**

The TAXI Direct-to-Disk interface, in conjunction with the Disk Recording System (DRS) software developed by the SSC Boeing group, supplies a solution that provides higher integrity data that can be processed and made available to the customer with hours. The TAXI Direct-to-Disk interface is a special purpose interface solution developed by ISC for demultiplexing data from a Racal Storeplex (or equivalent) multichannel recorder onto one or more hard disks that reside in, and/or are controlled by, a personal computer (PC). (The name “TAXI” is the acronym for “transparent asynchronous transceiver interface”). The installation of the TAXI Direct-to-Disk interface, in conjunction with other modifications, causes the transfer of data to be recorded directly to disk so it can be extracted and analyzed after the test.

The instrumentation is connected to the input terminals of the signal-processing unit of multichannel recorder by standard coaxial cables. The coaxial output of the signal-processing unit is converted to fiber-optic output by means of a commercial coaxial cable/fiber-optic converter (that is, a fiber-optic transceiver) designed by Omni Technologies specifically for this application. The fiber-optic link carries the data signals to an identical fiber-optic transceiver in the control room. On the way to the TAXI Direct-to-Disk interface, the data signals are processed through a companion special purpose circuit denoted by the similar name “parallel TAXI interface.”

The TAXI Direct-to-Disk interface is implemented by means of field-programmable gate arrays (FPGAs), memory chips, and other integrated circuits on a printed-circuit board



that conforms to the peripheral component interface (PCI) standard and is denoted on the TAXI-100 card. The TAXI-100 card performs real-time demultiplexing of the data signals from the parallel TAXI Direct-to-Disk interface to individual channel files within the host PC. The data is provided in a layered interface that consists of the TAXI physical layer with the Racal proprietary data format contained in the application layer. The application layer is stripped off by the parallel TAXI Direct-to-Disk interface. Parallel clock and data signals containing the Racal proprietary data format are received by the TAXI-100 card in the parallel format and demultiplexed, according to formats extracted from within the data. Other proprietary programmable logic chips provide for the management and buffering of the channel blocks until they are presented to the host PC across a PCI bus interface. Real-time software drivers running under the Microsoft NT 4.0 operating system provide for real-time handling of interrupts and buffering onto small computer systems interface (SCSI) disks in individual channel files. A host graphical user interface enables the user to select recorder channels.

A system of five TAXI-100 cards was implemented into the Stennis "A" test area High Speed Data Acquisition System (HDAS) to provide a Disk Recording System (DRS). The DRS consists of a "Bridge Computer", five Direct-to-Disk (DTD) recorders, and a Remote Control Panel Computer. While the TAXI-100 cards were developed to write data direct-to-disk, there were several additional requirements for integration into the test area system. These requirements included the ability to dynamically configure the DTD to record single or multiple channels and to start and stop the recorders from a control station remote from the DTD system. There were also requirements to be able to index the DTD data files to prevent overwriting of data and the ability to produce filtered

frequency data form time series DTD data files. To meet these requirements, the Stennis Boeing test operations group wrote the DRS integration software that ties together the complete DRS system.

## **RESULTS**

The DRS system implemented in the Stennis test area has monitored over 12 test firings to date with no malfunctions and has met or exceeded all expectations. The system has resulted in an ability to provide the high-speed data to the customer within an hour. The system requires less time for extracting the data (one hour compared to four to eight hours previously), which allows more time for data analysis. The result is the realization of a substantial savings in time, labor, and materials. There has also been an additional time saving in pretest preparation of the tapes, which is no longer required. In addition, there is increased data integrity due to the elimination of single sample errors experienced on occasion with the tape recording.

## **END USERS**

NASA is one of the largest users of the Racal Storeplex Recorders. Racal has decided to eliminate that product line. This system can be extended into other NASA test facilities where the Racal Recorders are used, as well as, any other industry users of the Racal Recorders.

## **DUAL USE**

The dual-use concept of product development is based on the sharing of costs, risks and successes between the government and a commercial partner. In these projects, NASA can contribute technology development, unique facilities and know how, engineering

resources, and potentially some part of the funding. In turn, the commercial partner contributes its unique resources, facilities, manufacturing, and marketing capabilities. The result is an approach that provides considerable flexibility, and draws upon the capabilities of both parties.

For more information on the NASA Dual-Use Technology Development Program at Stennis, call (228) 688-1929, or access the web site at <http://technology.ssc.nasa.gov>.



# Collecting Real-Time Test Data

## Integrated System Consultants, San Jose, CA.

### Innovation

-The TAXI Direct-to-Disk system provides high-speed data significantly faster with fewer errors than was previously available. Working through the Racal Storeplex system in conjunction with system integration software the TAXI-100 Direct-to-Disk replaces the previously used tape recordings.



**TAXI-100 Direct-to-Disk system as arrayed for use at the NASA Stennis test facility.**

### Accomplishments

- The TAXI-100 Direct-to-Disk interface is a special purpose interface circuit developed for demultiplexing data from a Racal Storeplex (or equivalent) multichannel recorder onto one or more hard disks that reside in, and/or are controlled by a personal computer.
- By extracting the data from the Racal front-end, the data can then be recorded directly to disk providing a media that requires less pretest maintenance and is less susceptible to sample recording errors.
- The Direct Recording System (DRS), through 12 test firings to date, has shown no malfunctions and has met or exceeded all expectations.

### Commercialization

- Development of the TAXI-100 Direct-to-Disk provides end users substantial savings in time, labor, and materials resulting in increased data integrity.
- This unique system can be extended to all test facilities, not just NASA test facilities, requiring high-speed data collection. NASA test facilities at Stennis Space Center provided a functional testing ground.

## Government/Science Applications

- The TAXI-100 Direct-to-Disk system provides high-speed data significantly faster with fewer errors than previously available to NASA test facilities.
- Enhances the Racal Storeplex system, by extracting the data from the Racal front-end the data can be stored directly to disk.

### Points of Contact:

Office of Technology Transfer (228) 688-1929  
ISC – Bruce Newman (408) 995-5421

Stennis Space Center  
April 26, 2002  
Success Story #2400488









# NASA Office of Technology Transfer

John C. Stennis Space Center

## Dual-Use Activity Answers Collection Problems

*Improvements to data collection software allows acquisition of real-time data necessary in testing rocket engines and other propulsion components.*



***Data Flow Architecture with Parallel Taxi Interface was implemented into the Stennis "A" test area High Speed Data Acquisition to provide a Disk Recording System (DRS).***

The TAXI-100 System was developed jointly by Integrated Systems Consultants (ISC) of San Jose, CA. and Omni Technologies of New Orleans, LA. under a Cooperative Agreement with the NASA Office of Technology Transfer. The system has real-time remote hardware demultiplexing capability that provides channelized data to the control station across a fiber optic link. This capability extends the present product lines of ISC and Omni to provide the direct-to-disk recording through the Racal Storeplex interface with the TAXI system.

High-speed data provides valuable information about tests conducted with rocket engines and other propulsion components. Providing timely access to this data has been an issue in the past. Through the Dual-Use Development Program at NASA's Stennis Space Center (SSC), direct-to-disk storing capabilities for high speed data acquisition systems are now available through Integrated Systems Consultant's TAXI-100 Direct-to-Disk system. The TAXI-100 Direct-to-Disk system works through the Racal Storeplex system in conjunction with system integration software, Disk Recording System (DRS), developed by Boeing test operations at SSC to provide the high speed data significantly faster with fewer errors than was available with the previously used Racal Storeplex recordings.

### HOT Points

- Provides timely access
  - Direct-to-disk storage capability
  - Reduces error
  - PC compatible
  - Increases data integrity
  - Utilizes fiber-optic link
- Provides time saving in pretest preparations**



The TAXI-100 Direct-to-Disk system was developed jointly by Integrated Systems Consultants (ISC) of San Jose, CA, and Omni Technologies of New Orleans, LA, under Cooperative Agreement NCC13-00006 with the NASA Office of Technology Transfer. The system has a real-time remote hardware demultiplexing capability that provides channelized data to the control station across a fiber optic link. The Cooperative Agreement between NASA, ISC and Omni, who developed the fiber optic interface, provides acquisition solutions for customers using coax to fiber conversion solutions such as the FOTR-125 fiber link. The TAXI-100 card developed by ISC provides PC-based direct-to-disk solutions for the Racal Storeplex system and other acquisition front-ends for industry where sustained data streams of 10 Mbytes per second or more are required.

## PROBLEM DESCRIPTION

NASA rocket testing at Stennis Space Center requires acquisition of high-speed data during tests with the ability to transfer high-volume data to remote control stations and engineering management. The control, recording, and post-processing equipment of the facility are located in a control room at a safe distance from the test stand. Heretofore, the transfer of data from the instrumentation to the post-processing equipment has entailed post-test downloading of the data from Racal tapes via software, requiring many hours to days of post-test reduction before the data could be viewed in a channelized format. In addition, hours were spent in pre-test preparation of the recording tapes to ensure their integrity. Despite these efforts, there were occasions where single sample errors were introduced into the data by the tapes.

The present high-speed data acquisition system uses Racal Storeplex Recorders, which are commercially available multichannel recorders. Racal methods involve the use of real-time programmable logic of the parallel bus within the Racal recorder. Without extensive modifications, the test stand configuration required that the high-speed data continue to route through the Racal Storeplex tape transport units.

One method of demultiplexing the data using the Racal Storeplex system required the fabrication of a new card as an interface to existing commercial off the shelf products (COTS) to extract the channelized data from the proprietary format. The TAXI bus is a serial-bus used between the Racal front-end and the recording unit. By extracting the data from the Racal front-end, the data can then be recorded directly to disk, which provides a recording media that requires less pretest maintenance and is less susceptible to sample recording errors.

## SOLUTION

The TAXI Direct-to-Disk interface in conjunction with the Disk Recording System (DRS) software developed by the SSC Boeing group supplies a solution that provides higher integrity data that can be processed and made available to the customer within hours. The TAXI Direct-to-Disk interface is a special purpose interface circuit developed by ISC for demultiplexing data from a Racal Storeplex (or equivalent) multichannel recorder onto one or more hard disks that reside in, and/or are controlled by, a personal computer (PC). (The name "TAXI" is the acronym for "transparent asynchronous transceiver interface"). The installation of the TAXI Direct-to-Disk interface, in conjunction with other modifications, causes the transfer of data to be recorded directly to disk so it can be extracted and analyzed after the test.

The instrumentation is connected to the input terminals of the signal-processing unit of multichannel recorder by standard coaxial cables. The coaxial output of the signal-processing unit is converted to fiber-optic output by means of a commercial coaxial cable/fiber-optic converter (that is, a fiber-optic transceiver) designed by Omni Technologies Inc specifically for this application. The fiber-optic link carries the data signals to an identical fiber-optic transceiver in the control room. On the way to the TAXI Direct-to-Disk interface, the data signals are processed through a companion special purpose circuit denoted by the similar name "parallel TAXI interface."

The TAXI Direct-to-Disk interface is implemented by means of field-programmable gate arrays (FPGAs), memory chips, and other integrated circuits on a printed-circuit board that conforms to the peripheral component interface (PCI) standard and is denoted the TAXI-100 card. The TAXI-100 card performs real-time demultiplexing of the data signals from the parallel TAXI Direct-to-Disk interface to individual channel files within the host PC. The data is provided in a layered interface that consists of the TAXI physical layer with the Racal proprietary data format contained in the application layer. The application layer is stripped off by the parallel TAXI Direct-to-Disk interface.

Parallel clock and data signals containing the Racal proprietary data format are received by the TAXI-100 card in the parallel format and demultiplexed, according to formats extracted from within the data. Other proprietary programmable logic chips provide for the management and buffering of the channel blocks until they are presented to the host PC across a PCI bus interface. Real-time software drivers running under the Microsoft NT 4.0 operating system provide for real-time handling of interrupts and buffering onto small computer systems interface (SCSI) disks in individual channel files. A host graphical user interface enables the user to select recorder channels.



A system of five TAXI-100 cards was implemented into the Stennis "A" test area High Speed Data Acquisition System (HDAS) to provide a Disk Recording System (DRS). The DRS consists of a "Bridge Computer", five Direct-to-Disk (DTD) recorders, and a Remote Control Panel Computer. While the TAXI-100 cards were developed to write data direct-to-disk, there were several additional requirements for integration into the test area system. These requirements included the ability to dynamically configure the DTD to record single or multiple channels and to start and stop the recorders from a control station remote from the DTD system. There were also requirements to be able to index the DTD data files to prevent overwriting of data and the ability to produce filtered frequency data form time series DTD data files. To meet these requirements, the Stennis Boeing test operations group wrote the DRS integration software that ties together the complete DRS system.

## **RESULTS**

The DRS system implemented in the Stennis test area has monitored over 12 test firings to date with no malfunctions and has met or exceeded all expectations. The system has resulted in an ability to provide the high-speed data to the customer within an hour. The system requires less time for extracting the data (one hour compared to four to eight hours previously), which allows more time for data analysis. The result is the realization of a substantial savings in time, labor, and materials. There has also been an additional time saving in pretest preparation of the tapes, which is no longer required. In addition, there is increased data integrity due to the elimination of single sample errors experienced on occasion with the tape recording.

## **END USERS**

NASA is one of the largest users of the Racal Storeplex Recorders. Racal has decided to eliminate that product line. This system can be extended into other NASA test facilities where the Racal Recorder are used, as well as, any other industry users of the Racal Recorders.

## **DUAL USE**

The dual-use concept of product development is based on the sharing of costs, risks and successes between the government and a commercial partner. In these projects, NASA can contribute technology development, unique facilities and know how, engineering resources, and potentially some part of the funding. In turn, the commercial partner contributes its unique resources, facilities, manufacturing, and marketing capabilities. The result is an approach that provides considerable flexibility, and draws upon the capabilities of both parties.

For more information on the NASA Dual-Use Technology Development Program at Stennis, call (228) 688-1929, or access the web site at <http://technology.ssc.nasa.gov>.

## **Points of Contact**

- **ISC Products**  
San Jose, CA.  
PH - 408 995-5421  
Web - [www.intsvscons.com](http://www.intsvscons.com)
- **Omni Technologies, Inc.**  
New Orleans, LA.  
PH - 540 288-8211  
Web - [www.oliengineering.com](http://www.oliengineering.com)
- **NASA Office of Technology Transfer**  
Stennis Space Center, MS.  
PH - 228 688-1929  
Web - [technology.ssc.nasa.gov](http://technology.ssc.nasa.gov)  
E-mail - [technology@ssc.nasa.gov](mailto:technology@ssc.nasa.gov)



REPORT DOCUMENTATION PAGE					Form Approved OMB No. 0704-0188	
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p><b>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</b></p>						
1. REPORT DATE (DD-MM-YYYY) 23-05-2002		2. REPORT TYPE			3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE Collecting Real-Time Test Data				5a. CONTRACT NUMBER NCC-00006		
				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S) Technology Development and Transfer Office				5d. PROJECT NUMBER		
				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Technology Development and Transfer Office					8. PERFORMING ORGANIZATION REPORT NUMBER  SE-2002-05-00042-SSC	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)					10. SPONSORING/MONITOR'S ACRONYM(S)	
					11. SPONSORING/MONITORING REPORT NUMBER	
12. DISTRIBUTION/AVAILABILITY STATEMENT Publicly Available STI per form 1676						
13. SUPPLEMENTARY NOTES periodical						
14. ABSTRACT						
15. SUBJECT TERMS						
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19b. NAME OF RESPONSIBLE PERSON	
a. REPORT	b. ABSTRACT	c. THIS PAGE			Technology Development and Transfer Office	
U		U	UU	8	19b. TELEPHONE NUMBER (Include area code) (228) 688-1929	